








	GRAY POURABLE CONCRETE CRACK FILLER	CONCRETE REPAIR	MORTAR REPAIR	AKONASEAL® POLYURETHANE MASONRY/JOINT SEALANT	AKONAFLEX® SELF-LEVELING CONCRETE REPAIR	AKONAFLEX® PRO SELF-LEVELING EXPANSION JOINT FILLER	EPOXY CRACK REPAIR
							
USES & ADVANTAGES	<ul style="list-style-type: none"> • Flexible • Economical acrylic • Width: ¼" max • Depth: ¼" max 	<ul style="list-style-type: none"> • Concrete texture • Skims over in 8 hours • Flexible/durable • Paintable (latex) • Width: ⅜" max • Depth: ⅜" max 	<ul style="list-style-type: none"> • Masonry texture • Skims over in 8 hours • Flexible/durable • Paintable (latex) • Width: ⅜" max • Depth: ⅜" max 	<ul style="list-style-type: none"> • Textured, water-resistant • Skims in 24 hours • Polyurethane/flexible • Paintable (latex) • Width: 1" max • Depth: ½" max 	<ul style="list-style-type: none"> • Smooth, water-resistant • Self-leveling (no tooling) • Polyurethane/flexible • Paintable (latex) • Width: 1" max • Depth: ½" max 	<ul style="list-style-type: none"> • Smooth, water-resistant • Self-leveling (no tooling) • Urethane/flexible • Paintable (latex) • Width: 1½" max • Depth: 1" max 	<ul style="list-style-type: none"> • Smooth finish • High-strength epoxy • Low-viscosity • Moisture tolerant • Width: ¼" max • Depth: 6" max
COVERAGE	<ul style="list-style-type: none"> • 1 qt. bottle fills 40 lin. ft. at ¼" deep x ¼" wide • 1 gal. bottle fills 160 lin. ft. at ¼" deep x ¼" wide 	<ul style="list-style-type: none"> • 10.1 oz. tube fills 10 lin. ft. at a ⅜"x⅜" joint 	<ul style="list-style-type: none"> • 10.1 oz. tube fills 10 lin. ft. at a ⅜"x⅜" joint 	<ul style="list-style-type: none"> • 10.1 oz. tube fills 12 lin. ft. at a ½"x¼" joint 	<ul style="list-style-type: none"> • 10.1 oz. tube fills 12 lin. ft. at a ½"x¼" joint • 29 oz. tube fills 34 lin. ft. at a ½"x¼" joint 	<ul style="list-style-type: none"> • 10.1 oz. tube fills 12 lin. ft. at a ½"x¼" joint • 29 oz. tube fills 34 lin. ft. at a ½"x¼" joint 	<ul style="list-style-type: none"> • Net 6 fl. oz. tube will yield approx. 10-11 cu. in.
APPLICATION							
Interior & Exterior	X	X	X	X	X	X	X
Wide or Expansion Joints				X	X	X	
Narrow Holes & Cracks	X	X	X				X
Water-Resistant	X	X	X	X	X	X	X
Vertical Applications		X	X	X			
Horizontal Applications	X	X	X	X	X	X	X
For Mortar, Stucco, Stone			X	X			
For Concrete Surfaces	X	X			X	X	X
Paintable	X	X	X	X	X	X	
VOC Compliant	X	X	X	X	X	X	
Available In 2 Sizes	X				X	X	