

Safety Data Sheet

SODAL Soudacryl LTX1 / Acryrub 1

Section 1. Identification

Product Identifier	SODAL Soudacryl LTX1 / Acryrub 1		
Synonyms	400405; 400404; 400403; 400402; 400401; 400400		
Manufacturer Stock Numbers	79295WH25		
Recommended use	Refer to Technical Information		
Uses advised against	Refer to Technical Information		
Manufacturer Contact Address	Soudal Accumetric 350 Ring RD Elizabethtown, KY, 42701 USA		
	Phone	Emergency Phone	Fax
	(270) 769-3385	(800) 424-9300 CHEMTREC	(270) 765-2412

Section 2. Hazards Identification

Classification	N/A
Signal Word	
Pictogram	
Hazard Statements	N/A
Precautionary Statements	
Response	N/A
Prevention	N/A
Storage	N/A
Disposal	N/A
General	If medical advice is needed, have product container or label at hand Keep out of reach of children

Read label before use

Ingredients of unknown toxicity	0%
Hazards not Otherwise Classified	
GHS Classification	Not a hazardous substance or mixture.
GHS Label Element	Not a hazardous substance or mixture.
Other hazards	None known

Section 3. Ingredients

CAS	Ingredient Name	Weight %
27138-31-4	Dipropylene glycol dibenzoate	1% - 5%
64742-46-7	Distillates (petroleum), hydrotreated middle	1% - 5%
13463-67-7	Titanium Dioxide	1% - 5%
7632-00-0	Sodium Nitrite	0.1% - Max

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Ingestion	No first aid should be needed.
Inhalation	Remove to fresh air. Seek medical attention if irritation persists.
Skin Contact	Wash affected area with soap and water.
Eye Contact	Immediately flush with large amounts of water. If irritation occurs, seek medical attention.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media	Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Fog
Unsuitable Extinguishing Media	None known
Unusual Fire or Explosion Hazards	Product will not burn, but may splatter if temperature exceeds boiling point of water. Dried solids can burn, giving off oxides of carbon.
Special Fire Fighting Procedures	Non-flammable (aqueous emulsion). After water evaporates, remaining material will burn. Breathing apparatus required when fighting fires in enclosed areas.

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release	Determine whether to evacuate or isolate the area according to your local emergency plan. Observe all personal protection equipment recommendations
---	---

described in Sections 5 and 8. For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. For small spills, wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled material, even in small quantities, may present a slip hazard. Final cleaning may require the use of steam, solvents or detergents. Dispose of saturated absorbent or cleaning materials appropriately, since spontaneous heating may occur.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Section 7. Handling and Storage

Storage Store in a cool dry place. Protect from freezing and excessive heat.

Handling Avoid breathing vapors in top of shipping container. Keep container closed. Use with adequate ventilation. Avoid contact with skin and clothing. Wash thoroughly after handling.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits	Ingredient Name	ACGIH TLV	OSHA PEL	STEL
	Dipropylene glycol dibenzoate	N/A	N/A	N/A
	Distillates (petroleum), hydrotreated middle	5 mg/m ³	5 mg/m ³	10 mg/m ³
	Titanium Dioxide	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust	N/A
	Sodium Nitrite	N/A	N/A	N/A

Personal Protective Equipment Goggles

Engineering Controls Local Ventilation: Recommended
General Ventilation: Recommended

Ventilation Local exhaust ventilation is recommended to maintain vapor level below TLV.

Respiratory Protection Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within exposure guidelines. Industrial Hygiene Personnel can assist in judging the adequacy of existing engineering controls.

Suitable Respirator:
General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits as determined by air sampling or are unknown, appropriate respiratory protection should be worn. Follow OSHA Respirator

Regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators.

Skin Protection

Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Suitable Gloves:

Silver Shield® 4H®

Eye Protection

Chemical goggles if liquid contact is likely, or safety glasses with side shields.

Note

These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions. For further information regarding aerosol inhalation toxicity, please refer to the guidance document regarding the use of silicone-based materials in aerosol applications that has been developed by the silicone industry (www.SEHSC.com).

Section 9. Physical and Chemical Properties

Physical State	Paste
Color	See product label
Odor	Slight acrylic odor
Odor Threshold	N/A
Solubility	Dilutable in wet stage
Partition coefficient Water/n-octanol	N/A
VOC%	28 g/L
Viscosity	N/A
Specific Gravity	1.62
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	Not determined
FP Method	N/A
pH	N/A
Melting Point	0C
Boiling Point	100C
Boiling Range	N/A
LEL	0.9
UEL	15.3
Evaporation Rate	Slower than n-Butyl acetate
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A

Vapor Pressure	Not determined
Vapor Density	Lighter than air

CARB Method 310

VOC Content: 28 grams/liter

Note

The above information is not intended for use in preparing product specifications. Contact Soudal Accumetric before writing specifications.

Section 10. Stability and Reactivity

Chemical Stability	Stable
Materials to Avoid / Incompatibility	None known
Hazardous polymerization	Will not occur
Conditions to avoid	None known

Section 11. Toxicological Information

Carcinogenicity	No ingredient in this product is an IARC, NTP or OSHA listed carcinogen.
Component Toxicology Information	No known applicable information.
Special Hazard Information on Components	No known applicable information.

Section 12. Ecological Information

Environmental Fate and Distribution	Complete information is not yet available.
Environmental Effects	Complete information is not yet available.
Fate and Effects in Waste Water Treatment Plants	Complete information is not yet available.

Section 13. Disposal

RCRA Hazard Class (40 CFR 261)	When a decision is made to discard this material, as received, is it classified as a hazardous waste? NO
	State or local laws may impose additional regulatory requirements regarding disposal.
	We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	Not regulated
DOT Classification	Not regulated
Packing Group	Not regulated
Air Shipment (IATA)	Not subject to IATA regulations.
Ocean Shipment (IMDG)	Not subject to IMDG code.

Section 15. Regulatory Information

	The contents of this MSDS comply with the OSHA Hazard Communication Standard 29 CFR 1910.1200.
TSCA Status	All chemical substances found in this product comply with the Toxic Substances Control Act inventory reporting requirements.
SARA Title III Section 302 Extremely Hazardous Substances	None
SARA Title III Section 304 CERCLA Substances dangereuses	None
SARA Title III Section 311/312	No components subject to 40 CFR 370
California Prop 65	White and Colors WARNING: This product can expose you to chemicals including Titanium Dioxide, which is known to the State of California to cause cancer, and Methanol, which is known to the State of California to cause birth defects and/or other reproductive harm. For more information, go to www.P65Warnings.ca.gov
	Clear WARNING: This product can expose you to chemicals including Ethyl Acrylate, which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov

Section 16. Other Information

Revision Date 5/17/2018

Disclaimer The data contained herein is based upon information that Soudal Accumetric believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.