



# SOUDAL

## Safety Data Sheet

### SOUDAL Soudafoam Door & Window Genius Gun

#### Section 1. Identification

Product Identifier SOUDAL Soudafoam Door & Window Genius Gun

Synonyms 461800

Manufacturer Stock Numbers 128990

Recommended use Refer to Technical Information

Uses advised against Refer to Technical Information

Manufacturer Contact

Address  
Soudal  
350 Ring RD  
Elizabethtown, KY, 42701  
USA

Phone  
(270) 769-3385

Emergency Phone  
(800) 424-9300  
CHEMTREC

Fax  
(270) 765-2412

#### Section 2. Hazards Identification

Classification

- CARCINOGENICITY - Category 2
- EYE DAMAGE/IRRITATION - Category 2A
- FLAMMABLE AEROSOLS - Category 1
- GASES UNDER PRESSURE - Liquefied gas
- SENSITIZATION - RESPIRATORY - Category 1
- SENSITIZATION - SKIN - Category 1
- SKIN CORROSION/IRRITATION - Category 2
- SPECIFIC TARGET ORGAN TOXICITY (Repeated Exposure) - Category 2
- SPECIFIC TARGET ORGAN TOXICITY (Single Exposure) - Category 3

Signal Word  
Pictogram

Danger



Hazard Statements

Causes serious eye irritation  
Causes skin irritation  
Contains gas under pressure; may explode if heated  
Extremely flammable aerosol  
May cause allergy or asthma symptoms or breathing difficulties if inhaled  
May cause an allergic skin reaction  
May cause damage to organs through prolonged or repeated exposure.  
May cause respiratory irritation.  
Suspected of causing cancer.

Precautionary Statements

Response

Call a poison center or doctor if you feel unwell.  
Get medical advice/attention if you feel unwell.  
If experiencing respiratory symptoms: Call a poison center/doctor.  
If exposed or concerned: Get medical advice/attention.  
If eye irritation persists: Get medical advice/attention.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If inhaled: If breathing is difficult, remove person to fresh air and keep comfortable for breathing.  
If on skin: Wash with plenty of soap and water.  
If skin irritation or rash occurs: Get medical advice/attention.  
Specific treatment (see label)  
Take off contaminated clothing and wash it before reuse.  
Wash contaminated clothing before reuse.

Prevention

Avoid breathing dust/fume/gas/mist/ vapors/spray.  
Contaminated work clothing must not be allowed out of the workplace.  
Do not handle until all safety precautions have been read and understood.  
Do not spray on an open flame or other ignition source.  
Keep away from heat.  
Obtain special instructions before use.  
Pressurized container: Do not pierce or burn, even after use.  
Use only outdoors or in a well-ventilated area.  
Wash hands thoroughly after handling.  
Wear eye protection/face protection.

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50C/122F.  
Protect from sunlight. Store in a well-ventilated place.  
Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.

Disposal

Dispose of contents/container in accordance with local, state and federal regulations.

Ingredients of unknown toxicity 0%

Hazards not Otherwise Classified

Other Hazards Gas/vapor spreads at floor level: Ignition hazard.

## Section 3. Ingredients

CAS	Ingredient Name	Weight %
75-28-5	Isobutane	5% - 10%
115-10-6	Dimethyl ether	5% - 10%
9016-87-9	Polymeric diphenylmethane diisocyanate	30% - 40%
63449-39-8	Chlorinated paraffin waxes and hydrocarbon waxes	20% - 30%
13674-84-5	2-Propanol, 1-chloro-, phosphate (3:1)	1% - 5%
74-98-6	Propane	1% - 5%

Occupational exposure limits, if available, are listed in Section 8.

## Section 4. First-Aid Measures

Inhalation	Remove person to fresh air and keep comfortable for breathing. If breathing is difficult, oxygen should be administered by qualified personnel. If experiencing respiratory symptoms: Call a POISON CENTER/doctor.
Skin	Wash with plenty of soap and water. Take off immediately all contaminated clothing and wash it before reuse. If skin irritation or rash occurs: Get medical advice/attention.
Ingestion	Rinse mouth. Call a POISON CENTER or doctor/physician if you feel unwell.
Eyes	Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a POISON CENTER or doctor/physician.
Most Important Symptoms/Effects	<p>Acute</p> <p>Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness.</p> <p>Delayed</p> <p>Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure: thyroid gland, liver.</p>
Indication of any immediate medical attention and special treatment needed	Treat symptomatically and supportively.

## Section 5. Fire Fighting Measures

Suitable Extinguishing Small fires: Quick-acting ABC-powder extinguisher, Quick-acting BC-powder

Media	extinguisher.
Unsuitable Extinguishing Media	Small fires: Quick-acting CO2 extinguisher, Water (water can be used to control jet flame), foam. In case of major fire and large quantities: Water (water can be used to control jet flame), foam.
Special Hazards Arising from the Chemical	Extremely flammable aerosol. Contains gas under pressure; may explode if heated. Pressurized container: Do not pierce or burn, even after use. May polymerize with evolution of heat.
Hazardous Combustion Products	On burning: Irritating and toxic gases or fumes may be released during a fire: oxides of carbon, phosphorus, hydrogen chloride, nitrous vapors. On heating: May release toxic gases and combustible. gases: hydrogen cyanide.
Advice for firefighters	Eliminate all sources of ignition. Do not spray on an open flame or other ignition sources. If safe to do so, move undamaged containers from the fire area. Keep unnecessary people away, isolate hazard area and deny entry. Cool containers with water from unmanned hose holder or monitor nozzles until well after fire is out. Let the fire burn. Stay away from the ends of tanks. Prevent entry into sewers, drains, ditches, underground or confined spaces and waterways. Avoid inhalation of material or combustion by-products.
Special Protective Equipment and Precautions for Firefighters	Wear full protective fire fighting gear including self contained breathing apparatus (SCBA) for protection against possible exposure.

## **Section 6. Accidental Release Measures**

Personal Precautions, Protective Equipment and Emergency Procedures	Wear personal protective clothing and equipment, see Section 8.
Methods and Materials for Containment and Cleaning Up	Eliminate all ignition sources if safe to do so. Stop leak if safe to do so. Reduce vapors with water spray. Small spills: Absorb spill with sand or other non-combustible material. Collect spilled material in appropriate container for disposal. Large spills: Dike for later disposal. Keep unnecessary people away, isolate hazard area and deny entry. Stay upwind and keep out of low areas.
Environmental Precautions	Avoid release to the environment.

## **Section 7. Handling and Storage**

Precautions for Safe Handling	Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Pressurized container: Do not pierce or burn, even after use. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Use only outdoors or in a well-ventilated area. Do not spray on an open flame or other ignition sources. Ground/Bond container and receiving equipment. Use explosion-proof electrical/ventilating /lighting equipment. Take action to prevent static discharges. Do not breathe vapor or spray. Use non-sparking tools. Contaminated work clothing must not be allowed out of the workplace. Do not eat, drink, or smoke when using this product. Wear protective gloves/protective clothing/eye protection/face protection. Wash thoroughly after handling.
-------------------------------	--

Conditions for Safe Storage, Including any Incompatibilities

Store in a well-ventilated place. Keep container tightly closed. Store locked up.

Incompatible Materials

strong acids, strong bases, amines

## Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits

Ingredient Name	ACGIH TLV	OSHA PEL	STEL
Isobutane	1000 ppm	N/A	1000 ppm
Dimethyl ether	N/A	400 ppm	N/A
Polymeric diphenylmethane diisocyanate	0.005 ppm	0.02 mg/m <sup>3</sup>	N/A
Chlorinated paraffin waxes and hydrocarbon waxes	N/A	N/A	N/A
2-Propanol, 1-chloro-, phosphate (3:1)	N/A	N/A	N/A
Propane	1000 ppm TWA	1000 ppm PEL	N/A

Personal Protective Equipment

Goggles, Gloves

ACGIH - Threshold Limit Values - Biological Exposure Indices (BEI)

There are no biological limit values for any of this product's components.

Engineering Controls

Ventilation equipment should be explosion-resistant if explosive concentrations of material are present. Provide local exhaust or process enclosure ventilation system. Ensure compliance with applicable exposure limits.

Individual Protection Measures, such as Personal Protective Equipment

Eye/face protection

Wear splash resistant safety goggles with a faceshield.

Skin Protection

Wear fire/flame resistant/retardant clothing. Refer to NFPA 2112, Standard on Flame-Resistant Garments for Protection of Industrial Personnel Against Flash Fire and NFPA 2113, Standard on the Selection, Use, Care and Maintenance of Flame-Resistant Garments for Protection of Industrial Personnel Against Short-duration Thermal Exposures from Fire (2015).

Respiratory Protection

If airborne contaminant levels may exceed recommended exposure limits, NIOSH approved respiratory protection appropriate for employee exposure levels is recommended. Consult with a health and safety professional for specific respirators appropriate for your use.

Glove Recommendations

Wear appropriate chemical resistant gloves.

## Section 9. Physical and Chemical Properties

Physical State	Aerosol
Color	Champagne
Odor	Characteristic
Odor Threshold	Not available
Solubility	Insoluble in water
Partition coefficient Water/n-octanol	Not available
VOC%	18% (by wt) 175 g/L
Viscosity	No data available
Specific Gravity	0.92 at 20C
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	Not available
FP Method	N/A
pH	Not available
Melting Point	Not available
Boiling Point	Not available
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Not available
Flammability	Extremely flammable aerosol
Decomposition Temperature	Not available
Auto-ignition Temperature	Not available
Vapor Pressure	Not available
Vapor Density	>1 (relative)

Note The above information is not intended for use in preparing product specifications. Contact Soudal before writing specifications.

## Section 10. Stability and Reactivity

Reactivity	Reacts violently with acids bases. May be ignited by heat, sparks or flames. Gas/vapor spreads at floor level: Ignition hazard.
Chemical Stability	Stable under normal conditions of storage and handling.
Possibility of Hazardous Reactions	May polymerize: strong bases, amines.
Conditions to Avoid	Keep away from heat, sparks and naked flames. Keep away from ignition sources - No smoking. Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. Avoid contact with incompatible materials.
Incompatible Materials	strong acids, strong bases, amines

**Hazardous decomposition products** On heating. May release toxic gases, combustible gases, vapors: hydrogen cyanide. On burning: Irritating and toxic gases or fumes may be released during a fire: oxides of carbon, phosphorus, hydrogen chloride, nitrous vapors.

## Section 11. Toxicological Information

### Information on Likely Routes of Exposure

#### Inhalation

May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause respiratory irritation.

#### Skin Contact

Causes skin irritation. May cause allergic skin reaction.

#### Eye Contact

Causes serious eye irritation. May cause redness, pain, and tearing.

#### Ingestion

No information on significant adverse effects.

### Component Analysis - LD50/LC50

The components of this material have been reviewed in various sources and the following selected endpoints are published:

Polymethylene polyphenylene isocyanate (9016-87-9)

Oral LD50 Rat 49 g/kg

Dermal LD50 Rabbit >9.4 g/kg

Inhalation LC50 Rat 11 mg/L 4 h

Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8)

Oral LD50 Rat >21500 µL/kg

Glyceryl polypropylene glycol triether (25791-96-2)

Oral LD50 Rat 2830 µL/kg

Dermal LD50 Rabbit >20 mL/kg

Isobutane (75-28-5)

Inhalation LC50 Rat 658 mg/L 4 h

Dimethyl ether (115-10-6)

Inhalation LC50 Rat 164000 ppm 4 h

2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5)

Oral LD50 Rat 1500 mg/kg

Dermal LD50 Rabbit >5000 mg/kg (no deaths occurred )

Inhalation LC50 Rat >5.05 mg/L 4 h

Propane (74-98-6)

Inhalation LC50 Rat >800000 ppm 15 min

### Acute and Chronic Toxicity

#### Immediate Effects

Causes skin irritation. Causes serious eye irritation. May cause allergy or asthma symptoms or breathing difficulties if inhaled. May cause an allergic skin reaction. May cause respiratory irritation. May cause drowsiness or dizziness.

Delayed Effects  
Suspected of causing cancer. May cause damage to organs through prolonged or repeated exposure: thyroid gland, liver.

Irritation/Corrosivity Data  
eye irritation, skin irritation, respiratory tract irritation

Respiratory Sensitization  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Dermal Sensitization  
May cause an allergic skin reaction

Germ Cell Mutagenicity  
No information available for the product.

Tumorigenic Data  
No information available for the product.

Reproductive Toxicity  
No information available for the product.

Specific Target Organ Toxicity - Single Exposure  
No target organs identified.

Specific Target Organ Toxicity - Repeated Exposure  
liver, thyroid gland

Aspiration hazard  
Not expected to be an aspiration hazard.

Medical Conditions Aggravated by Exposure  
No information available for the product.

#### Product Toxicity Data

Acute Toxicity Estimate  
Dermal > 2000 mg/kg  
Oral > 2000 mg/kg

#### Component Carcinogenicity

Polymethylene polyphenylene isocyanate 9016-87-9  
IARC: Supplement 7 [1987] ; Monograph 19 [1979] (Group 3 (not classifiable))  
DFG: Category 4 (no significant contribution to human cancer )

Chlorinated paraffin waxes and hydrocarbon waxes 63449-39-8  
IARC: Monograph 48 [1990] (Group 2B (possibly carcinogenic to humans))  
DFG: Category 3B (could be carcinogenic for man )  
OSHA: Present

Suspected of causing cancer.

## Section 12. Ecological Information

#### Component Analysis -

Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8)



## Aquatic Toxicity

Fish:  
LC50 96 h *Lepomis macrochirus* >300 mg/L [static ]  
LC50 96 h *Oncorhynchus mykiss* >0.0109 mg/L [flow-through ]  
LC50 96 h *Oncorhynchus mykiss* 94.5 - 271 mg/L [static ]  
LC50 96 h *Lepomis macrochirus* >0.1 mg/L [flow-through ]  
LC50 96 h *Pimephales promelas* >100 mg/L [static ]

2-Propanol, 1-chloro-, phosphate (3:1) (13674-84-5)

Fish:  
LC50 96 h *Brachydanio rerio* 56.2 mg/L [static ]  
LC50 96 h *Pimephales promelas* 98 mg/L [static ]  
LC50 96 h *Poecilia reticulata* 30 mg/L [static ]

Algae:  
EC50 72 h *Desmodesmus subspicatus* 45 mg/L IUCLID  
EC50 96 h *Pseudokirchneriella subcapitata* 4 mg/L IUCLID

Invertebrate:  
EC50 48 h *Daphnia magna* 63 mg/L IUCLID

## Persistence and Degradability

Not readily biodegradable (according to OECD criteria).

## Bioaccumulative Potential

No information available for the product.

## Mobility in Soil

No information available for the product.

## Bioconcentration

No information available for the product.

## Other Toxicity

No additional information available for the product.

## Section 13. Disposal

### Disposal Methods

Dispose of contents/container in accordance with local/regional/national /international regulations.

### Component Waste Numbers

The U.S. EPA has not published waste numbers for this product's components.

## Section 14. Transport Information

### UN Number

1950

### UN Proper Shipping Name

AEROSOLS

### DOT Classification

Hazard Class 2.1

### Packing Group

2.1

### IATA Information

Shipping Name: AEROSOLS, FLAMMABLE  
Hazard Class: 2.1  
UN#: UN1950  
Required Label(s): 2.1

### ICAO Information

Shipping Name: AEROSOLS, FLAMMABLE  
Hazard Class: 2.1  
UN#: UN1950  
Required Label(s): 2.1

International Bulk  
Chemical Code

This material contains one or more of the following chemicals required by the IBC Code to be identified as dangerous chemicals in bulk.  
Polymethylene polyphenylene isocyanate (9016-87-9)  
IBC Code: Category Y  
Glyceryl polypropylene glycol triether (25791-96-2)  
IBC Code: Category Z

## Section 15. Regulatory Information

**U.S. Federal Regulations** This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), and/or require an OSHA process safety plan.

Polymethylene polyphenylene isocyanate (9016-87-9)  
SARA 313: 1 % de minimis concentration

SARA Section 311/312 (40 CFR 370 Subparts B and C) reporting categories  
Flammable; Gas Under Pressure; Carcinogenicity; Skin Corrosion/Irritation;  
Respiratory/Skin Sensitization; Serious Eye Damage/Eye Irritation; Specific  
Target Organ Toxicity

**U.S. State Regulations** The following components appear on one or more of the following state hazardous substances lists:

Polymethylene polyphenylene isocyanate (9016-87-9)  
NJ

Chlorinated paraffin waxes and hydrocarbon waxes (63449-39-8)  
MA

Isobutane (75-28-5)  
MA, NJ, PA

Dimethyl ether (115-10-6)  
MA, MN, NJ, PA

Propane (74-98-6)  
MA, MN, NJ, PA

**California Safe Drinking Water and Toxic Enforcement Act (Proposition 65)** Not listed under California Proposition 65.

## Section 16. Other Information

Revision Date 10/17/2019

HMIS and NFPA Rating  
HMIS  
Health: 2\*  
Fire: 3  
Reactivity: 0

NFPA  
Health: 2  
Fire: 3  
Reactivity: 0

Hazard Scale:  
0 = Minimal  
1 = Slight  
2 = Moderate  
3 = Serious  
4 = Severe  
\* = Chronic hazard

## Disclaimer

The data contained herein is based upon information that Soudal believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.